

# Payanywhere Smart Keypad

## Specifications | PAX A80



PAX A80

|                         |   |
|-------------------------|---|
| <b>OS</b>               | PayDroid powered by Android 6.0/7.1   |
| <b>Processor</b>        | Quad-core Cortex A53, 1.2 GHz   |
| <b>Memory</b>           | 1GB DDR + 8GB eMMC   1 x Micro SD card slot, supporting up to 32GB  |
| <b>Payment Module</b>   | Magstripe, EMV chip card, and NFC contactless card reader   |
| <b>Camera</b>           | 0.3 Megapixel, front facing   |
| <b>Display</b>          | 4-inch TFT WVGA 800 x 480 pixels   Multi-point capacitive touchscreen   |
| <b>Audio</b>            | 1 x speaker   |
| <b>Physical buttons</b> | 10 x numeric keys   5 x function keys   |
| <b>Communications</b>   | Serial, Ethernet, USB   |
| <b>Peripheral ports</b> | RS232   1 x PSTN   1 x Ethernet   1 x PINpad   1 x Micro USB 2.0, OTG   1 x Host USB 2.0  |
| <b>Printer</b>          | Printer speed: 50 lines/sec   Paper roll outer diameter: 50mm (2in)   |
| <b>Battery</b>          | 720mAh, 7.4V  |
| <b>Adapter</b>          | Input: 100 - 240V AC, 50Hz/60Hz<br>Output: 9.0V DC, 1.0Aw   |
| <b>Physical</b>         | L x W x H (in): 7.12 x 3.3 x 3.19   Weight (lb): 0.81<br>L x W x H (cm) 18.1 x 8.4 x 8.1   Weight (kg): 0.37  |
| <b>Environmental</b>    | 0°C - 50°C (32°F - 122°F) operating temperature<br>-20°C - 70°C (-4°F - 158°F) storage temperature<br>10% - 93% relative humidity   |
| <b>Certifications</b>   | PCI PTS 5.x SRED   EMV L1 & L2   EMV Contactless L1   Visa payWave   MasterCard Contactless   American ExpressPay   Discover D-PAS   JCB J/Speedy   Interac Flash L2   IC MasterCard TQM   CE   RoHs   UL   FCC |